



ISD-58P0010P0A

Article-No.: 220196

1/1,7" Network Dome, Fix,
Day/Night, 3840x2160, H.265,
1,29mm, 360°, IP66

Specifications

Camera type	Dome
Resolution standard	4K Ultra HD
System	True Day&Night
Imager	CMOS
Imager	Sony STARVIS, Sensor IMX226
Sensitivity	0,3 Lux
Sensitivity	at F2.8
Automatic electronic shutter (ESC)	1~1/10.000sec.
Manual electronic shutter (MES)	1~1/10000Sek.
Digital Noise Reduction (DNR)	yes
Low speed shutter	yes
Low speed shutter	automatic
White balance	automatic, fluorescent, outdoor, manual, incandescent
Backlight compensation	BLC
Wide Dynamic Range (WDR)	WDR 120dB
IR cut filter	switchable
Day/Night switching	auto, day, night
Resolution max.	3840x2160
Resolution	3840x2160 (16:9), 3072x2048 (4:3), 2592x1944 (4:3), 2592x1520 (16:9), 2560x1440 (16:9), 1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3), 352x256 (4:3), 352x240 (4:3), 320x240 (4:3)
Image transmission rate max.	30 fps
Motion detector	yes
Analysis functions	activity detection, motion analysis, tampering protection, Trip wire plus object counting, loitering detection, intrusion, Human detector, Defog
Text display	supplied
Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.40cm
Audio support	yes
Audio	2 Way Audio
Audio standards	G.711
Alarm inputs	1

Specifications (continued)

Alarm outputs	1
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out
Internal storage	microSD card, microSDXC card
Compression standard	H.264, H.265, H.264+, H.265+, M-JPEG
Stream types	Quad Streaming
Ethernet interface	10Base-T, 100Base-TX
Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS
Multicast compliant	yes
Lens type	fixed focal length
Focal length	1,29 mm
Horizontal angle of view	360°
Aperture range	F2,4
Digital zoom	yes
Illumination	infrared
Illumination	6x LEDs 850nm
Remote configuration	web browser
Password protection	yes
Supply voltage	12VDC, PoE
Power over Ethernet	IEEE 802.3af
Blower	no
Heater	no
Mounting	wall mount, ceiling mount
Temperature range (operation)	-20°C ~ +50°C
Housing material	plastic
Colour (housing)	white
Protection rating	IP66
ONVIF	ONVIF Profile S
Dimensions (HxWxD)	58,7x151,4mm
Parts supplied	manual, eneo Site Manager, bag of screws

Your partner for eneo products:

