

ICB-68M3611M5A

SKU: 220592



1/2,5" Network Camera 3840x2160, Day&Night, DOL-WDR 3,6-11mm, Infrared, IP67

Abb. ähnlich

Main Features

- 1/2.5" Sony STARVIS CMOS sensor
- 4K UHD Resolution 3840x2160, @25/30fps
- Motorised varifocal lens 3,6~11mm
- DOL-WDR (120dB) by triple scan images at 30/25fps
- VCA video analysis, ONVIF event mapping
- Browser independent (IE, Edge, Safari, Firefox, Chrome)

- Smart Codec H.265 ROI (Region of interest)
- Quad Smart Streaming: H.265(+), H.264(+), MJPEG
- Micro SD Card, HTML5 replay, Audio, Alarm
- Power supply PoE IEEE 802.3af
- Integrated connection box with sabotage contact
- Supports ONVIF Profile S and Profile T

Specifications

| | |
|---------------------------------|----------------------------------|
| Series | eneo Candid Small,eneo LN-Series |
| Camera: | |
| Camera type | Bullet |
| Sensor size | 1/2.5" |
| Resolution Standard | 4K Ultra HD |
| Imager | CMOS, Sony STARVIS,Sensor IMX274 |
| System | True Day&Night |
| Sensitivity | 0,2 Lux, at F1.5,40IRE |
| Low Speed Shutter | yes |
| Low speed shutter | 1x~10x |
| Manual electronic shutter (MES) | 1/25 ~ 1/10000sec. |

ICB-68M3611M5A

Continuation of the specifications

| | |
|------------------------------------|---|
| Automatic electronic shutter (ESC) | 1/25 ~ 1/10.000sec. |
| Wide Dynamic Range (WDR) | DOL-WDR 120dB,D-WDR |
| Flickerless function | yes |
| Backlight Compensation | BLC,HLC |
| Day&Night switch | ICR |
| Day&Night mode | auto,day,night,night-color mode,extern (Sensor) |
| White balance | ATW-Indoor,ATW-Outdoor>manual,Fluorescent light,Light bulb,Shade,Clear Sky,Flammes |
| Signal-to-noise ratio | 50dB |
| Video: | |
| Resolution | 3840x2160 (16:9),2592x1520 (16:9),1920x1080 (16:9),1600x900 (16:9),1280x720 (16:9),960x540 (16:9),640x360 (16:9),320x180 (16:9) |
| Image resolution max. | 3840x2160 |
| Image display | VerticalView 90°/270°,4:3,16:9 |
| Stream types | Multi Streaming |
| Image Transmission Rate | 30 fps |
| Video compression | H.264,H.264+ (Smart Stream),H.265,H.265+ (Smart Stream),M-JPEG |
| Lens: | |
| Lens Type | Varifocal (motorized) |
| Zoom Factor | 3x |
| Focal Length | 3,6 - 11 mm |
| Digital Zoom | yes |
| MOD (Minimum Object Distance) | 0,5 m |
| Iris Control | DC |
| Vertical Angle of View | 46 - 21° |
| Horizontal Angle of View | 84 - 40° |
| DORI: | |
| Detect (25px/m) | 85,3 - 211,1 m |
| Observe (62 px/m) | 34,2 - 85 m |
| Recognize (125 px/m) | 16,9 - 42,3 m |
| Identify (250 px/m) | 7,9 - 20,8 m |
| Functions: | |
| Multicast compliant | yes |
| Motion Detector | yes |
| Analysis functions | motion detection,Field detection,Object left,removed,Defog,Line detection |
| Alarm processing | recording internal storage,E-Mail,HTTP,FTP,Boost,TCP,UDP,Onvif Event Mapping,alarm out |
| Audio support | yes |
| Audio | 2 Way Audio |

ICB-68M3611M5A

Continuation of the specifications

| | |
|-------------------------------|--|
| Password protection | yes |
| e-PTZ support | yes |
| Internal storage | microSDHC card,microSDXC card |
| Menu languages | English,German,French,Korean |
| Privacy zone masking | Areas-ON/OFF switchable |
| Remote configuration | web browser |
| Web browser | MS internet Explorer: ActiveX ex 9.0,Safari: MJPEG,Mozilla: MJPEG,Google Chrome: MJPEG,Edge: MJPEG |
| User interface | Type A (orange / grey) |
| Mirror function | mirror,flip |
| Digital Noise Reduction | yes |
| Network: | |
| Network protocols | TCP/IP,UDP,IPv4,IPv6,HTTP,HTTPS,FTP,UPnP,RT P,RTSP,RTCP,DHCP,ARP,Zeroconf,Bonjour |
| Interfaces / Inputs/ Outputs: | |
| Video outputs | no |
| External connectors | micro SD card slot,Connection board (LSA, RJ45, audio, I / O alarm & Sabotage contacts) |
| Ethernet interface | 10Base-T,100Base-TX |
| Alarm inputs | 1 |
| Alarm outputs | 1 |
| Serial interfaces | Ethernet |
| General: | |
| Dimensions (HxWxD) | 130,50x82,15x265,80mm |
| Weight | 1.25kg |
| Illumination | infrared |
| Illumination | 4x High Power LEDs 850nm |
| Illumination range | approx. 40m |
| Color (housing) | Pantone Cool Gray 1C |
| Housing | outdoor |
| Housing material | aluminium |
| Integrated wall mount | yes |
| Power consumption | 9,2W |
| Blower | yes |
| Mounting | wall mount,ceiling mount |
| ONVIF | ONVIF Profile S,ONVIF Profile T |
| Power over Ethernet | IEEE 802.3af |
| Window heater | no |
| Protection rating | IP67 |
| SDK | upon request |
| Sunshield | yes |
| Supply voltage | PoE |

ICB-68M3611M5A

Continuation of the specifications

| | |
|-----------------------|---|
| Operating temperature | -50°C ~ +50°C |
| Text display | supplied |
| Vandal proof | no |
| Parts supplied: | |
| Parts supplied | manual,bag of screws |
| Notes: | |
| Special features | Integrated connection box with sabotage alarm contact,Simple wiring, the integrated connection board offers the possibility of network cabling via LSA connection bar or RJ45 socket.Terminal block for connection of alarm contacts and audio. |

Optional Accessory

| SKU | Name | Description |
|--------|-------------------|---|
| 218218 | eneo Site Manager | Management Software for eneo IP products |
| 216469 | IAD-5SG1004MUA | Gigabit Switch, Unmanaged, 60W, 4x PoE, 2x RJ45, 10/100/1000 Mbps, Desktop |
| 216472 | IAD-5SG1008MUA | Gigabit Switch, Unmanaged, 120W, 8x PoE, 1xSFP, 1x RJ45, 10/100/1000 Mbps, Desktop |
| 214459 | IAM-5SE1008MUA | Ethernet Switch, 8xPoE 100Mbps 1x RJ45, and 1x SFP 1000Mbps, Unmanaged, Industrial Design |
| 214460 | IAR-7SE1024MMA | Gigabit Switch, 2x RJ45, 24x PoE 100Mbps, 2xSFP 1000Mbps, 390W, Managed, 19", 1U |
| 202641 | PM-42A | Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4 |



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

