



# ICB-62M0550MAA

SKU: 231833



Abb. ähnlich

1/2.8" Netzwerk Camera, 1920x1080, Day/Night, DOL-WDR, 5.0-50mm, Infrared, IP67

## Main Features

1/2.8" Sony STARVIS CMOS Sensor

Excellent light sensitivity

Resolution max. 1920x1080 (Full HD)

Motorised varifocal lens 5.0~50mm

DOL-WDR (120dB) by triple scan images at 30/25fps

Motion Detection, Privacy Zones, Slow Shutter

Browser independent (IE, Edge, Safari, Firefox, Chrome)

Smart Codec H.265 ROI (Region of Interest)

Supports ONVIF Profile S and Profile T

Vertical View 90°/270° Modus, H-Flip, Mirror

Power supply PoE, IP67

Integrated connection box including connection board

## Specifications

Dimensions (HxWxD)	130,50x82,15x265,80mm
Series	eneo AN-Series
Resolution Standard	HD 1080p
System	True Day&Night
Sensor size	1/2.8"
Imager	CMOS
Video compression	H.264, H.264+ (Smart Stream), H.265, H.265+ (Smart Stream), M-JPEG
Image resolution max.	1920x1080
Image Transmission Rate	30 fps
Day&Night Switch	ICR

# ICB-62M0550MAA

Continuation of the specifications

Sensitivity	0,001 Lux
Sensitivity 2	40IRE, at F1.6
Low Speed Shutter	yes
Digital Noise Reduction	yes
Backlight Compensation	BLC, HLC
Wide Dynamic Range (WDR)	D-WDR, DOL-WDR 120dB
Motion Detector	yes
Lens Type 2	Varifocal (motorized)
Focal Length	5 - 50 mm
Iris Control	DC
Zoom Factor	10x
Digital Zoom	yes
Horizontal Angle of View	49,9 - 8°
Vertical Angle of View	26,7 - 4,5°
Illumination	infrared
Housing	outdoor
Color (housing)	Pantone Cool Gray 1C
Housing material	aluminium
Blower	yes
Video outputs	no
Alarm inputs	1
Alarm outputs	1
Audio support	no
Ethernet interface	100Base-TX, 10Base-T
Serial interfaces	Ethernet
Internal storage	microSDHC card, microSDXC card
Analysis functions	motion detection, tampering protection
Mounting_4	ceiling mount, wall mount
Supply voltage	PoE
Power consumption	9W, PoE
Power over Ethernet	IEEE 802.3af
Vandal proof	no
Operating temperature	-50°C ~ +50°C
Protection rating	IP67
ONVIF	ONVIF Profile S, ONVIF Profile T
Camera built	Bullet
Remote configuration	web browser
Illumination range	approx. 40m
Weight	1.3kg
Manufacturer order number	231833

## ICB-62M0550MAA

### Optional Accessory

SKU	Name	Description
218218	eneo Site Manager	Management Software for eneo IP products
202641	PM-42A	Pole mount adaptor for eneo Candid, Candid S, Candid M, WB1, AK-5, AK-4

### Optional Services

SKU	Name	Description
229234	CON-KAM-IPKON	Preconfiguration 1x IP camera Function test, FW update
211123	CUS-SL-B	Extra charge for special paint bullet camera in RAL color
214441	CUS-SL-GK	Painting basic costs once per RAL color and delivery lot

### Your contact person

SARL GENITECH  
108 Rue Henri Barbusse  
95100 Argenteuil  
FR  
Tel: 0139472651  
E-Mail: [genitech@genitech.fr](mailto:genitech@genitech.fr)  
Web: [www.genitech.fr](http://www.genitech.fr)

