

AW-UE20W **AW-HE20W** [White Model]
AW-UE20K **AW-HE20K** [Black Model]
4K Integrated Camera HD Integrated Camera For Indoor Use



Entry models suitable for use in huddle room and small classrooms

Camera performance and functions that provide the feeling of “being in the same room” during online meetings

Boasting high image quality, wide-angle coverage of up to 71° horizontal and a max. 12x optical zoom, the UE20/HE20 clearly captures the facial expressions of participants in a meeting. The UE20 / HE20 enables more comfortable online communication.

Excellent system flexibility to achieve smart wiring and smooth operation

By using a Panasonic remote camera controller or linking with software, the cameras can be easily installed, managed and operated. The UE20/HE20 enables a simple system configuration and facilitates installation.

Compact size and excellent functionality that do not disturb the existing video streaming environment

The compact camera realizes space-saving installation. The UE20/HE20 is suitable for replacing an existing camera or for expanding the current system.



Various features and functions to deliver flexibly to any video shooting needs.

Supports 4 interfaces.

The UE20/HE20 supports four output interfaces—3G-SDI, HDMI, IP and USB—so it can be used with a wide range of devices.

Allows expansion of existing system

The UE20/HE20 supports multiple outputs so that it can be used in combination with an existing system/equipment.

Ideal for online meetings

The UE20/HE20 supports UVC* so the video and audio signals can be output over USB. By using the PTZ Virtual USB Driver software and connecting with a LAN cable, it is possible to use the UE20/HE20 as a USB camera.

Linkage with Panopto software is also possible.

* UVC: USB video class
A standard for connecting video-handling devices such as webcams to a computer via USB.

Supports Panasonic software.

The UE20/HE20 supports the PTZ Control Center to improve workflow efficiency at video shooting sites.

Single controller*1 can control up to 200 camera units.

By using devices compatible with PoE+*2 for network connection, the video, audio and control signals as well as the power supply can be transmitted via single LAN cable.

*1 When AW-PR150GJ or AW-RP60 remote camera controller is used

*2 Abbreviation for Power over Ethernet Plus

Other Features

- RTMP/RTMPS for direct streaming.
- Operable from Web GUI.

Specifications

	AW-UE20W/K	AW-HE20W/K
Comprehensive		
Power Requirements	DC12 V ± 10 % (10.8 V to 13.2 V) (Supplied AC adapter)	
PoE+	IEEE802.3 at compliant	
Camera part		
Image Sensors	1/2.8-type MOS×1	
Lens	Electric 12 x optical zoom F1.6~F2.8 (f = 3.9 mm ~ 46.8 mm)	
Zoom magnification	Optical zoom: 12 x	
Angle of View Range	Horizontal angle of view: 71° (wide) to 6° (tele) Vertical angle of view: 43° (wide) to 3° (tele) Diagonal angle of view: 79° (wide) to 7° (tele)	
Output Format	HDMI	4K
		2160/30p, 2160/29.97p, 2160/25p
		HD
		1080/60p, 1080/59.94p, 1080/50p, 1080/60i, 1080/59.94i, 1080/50i, 1080/30p, 1080/29.97p, 1080/25p, 720/60p, 720/59.94p, 720/50p
	SDI	
		1080/60p, 1080/59.94p, 1080/50p, 1080/60i, 1080/59.94i, 1080/50i, 1080/30p, 1080/29.97p, 1080/25p, 720/60p, 720/59.94p, 720/50p
Output		
Video Output	HDMI, 3G-SDI OUT	
Input/output		
Input/Output Connector	LAN, RS-422, AUDIO IN, USB, RS-232C IN, RS-232C OUT	
Rotating platform part		
Pan operating range	±170°	
Tilt operating range	-30°~90° *1	
IP Streaming		
Image Streaming Mode	JPEG(MJPEG), H.264, H.265	
Image resolution	3840×2160, 1920×1080, 1280×720, 640×360	1920×1080, 1280×720, 640×360

*1 The main unit may appear in the video depending on the pan/tilt position.

*This specification is a part. Please see the website for details.

Accessories



Remote Camera Controller AW-RP150GJ

High operability ensured through touch-panel GUI monitor and a new type of joystick.



Remote Camera Controller AW-RP60GJ

Equipped with a GUI menu screen for clear visibility and a joystick for intuitive control.



Visual Preset Software Key AW-SF300G

GUI screen that enables the subject of multiple PTZ Cameras to be switched with a single click of an icon.

Panasonic®

Panasonic Corporation
Connected Solutions Company

2-15 Matsuba-cho, Kadoma, Osaka 571-8503 Japan

SP-UE/HE20PEWEB2 202110SP



Factories of AVC Networks Company have received ISO 14001:2004-the Environmental Management System certification. (Except for 3rd party's peripherals.)



For more information, please visit
Panasonic web site

https://pro-av.panasonic.net/en/?cid=ad_qr-mz_prd_mebd-ue80_211012_all_s_gl



Broadcast and
Professional
AV Website



Contact
Information



Facebook



Mobile App