SONY











BRC-X400 SRG-X400 SRG-X120

Sony's first IP 4K PTZ camera, with NDI® | HX capability and excellent picture quality delivered by superb Exmor R CMOS sensor

BRC-X400 for Broadcasting and Event Production

Excellent picture quality shooting

- 1/2.5 type 4K Exmor R sensor
- Up to 80x (FHD)/30x (4K) with 70° wide shooting angle
- 1700 TV line (4K) (Center)/1000 or higher TV line (HD) (Center)

Flexible and efficient IP-based live production

- NDI®*|HX capability (option)
- PoE+/image output/camera control via network cable
- Remote viewing (RTSP/RTMP**)

Easy system configuration and operation

- Genlock support and tally lamp
- Supporting multiple camera control protocols
- Scene file function**
- * NDI® is a registered trademark of NewTek, Inc.
- ** By future upgrade planned in early 2020

SRG-X400/X120 for Corporate and Education

Excellent picture quality shooting

- 1/2.5 type 4K Exmor R sensor
- Up to 40x (FHD)/30x (4K*) (X400), up to 12x (4K/FHD) (X120)
- 70° wide shooting angle

Flexible and efficient IP-based live production

- NDI®**|HX capability (option)
- PoE+/image output/camera control via network cable
- Remote viewing (RTSP/RTMP***)

Easy system configuration and operation

- Fast pan-tilt movement during preset
- Picture Freeze Preset function
- PTZ Sync function***
- * By optional license
- ** NDI® is a registered trademark of NewTek, Inc.
- *** By future upgrade planned in early 2020

Specifications

Model Name	BRC-X400	SRG-X400	SRG-X120
Video Output	3G-SDI, HDMI and IP streaming *4K output only via HDMI and IP streaming		
Zoom Ratio	30x (4K with CIZ)/40x (HD with CIZ), (Digital 12x) 12x (4K/HD), (Digital 12x)		12x (4K/HD), (Digital 12x)
Image Sensor	1/2.5 Exmor R CMOS		
Minimum Illumination (50IRE)	1.6 lux (50IRE, F2.0 30fps)		
Signal System (Max)	3840 x 2160 29.97p/1080 59.94p	3840 x 2160 29.97p (optional license)/1080 59.94p	
Horizontal Viewing Angle (Wide)	Approx. 70 degrees		
Pan/Tilt Range	P : ±170 T: +90, -20		
Max Preset Speed [deg/s]	300°/sec (Pan), 126°/sec (Tilt)		
Number of Preset	256 (CGI)		
Picture Freeze Preset	Yes		
Body Color	Black and White		
Control Interface	VISCA, VISCA over IP, S700PTP, CGI		
PoE+	Yes (IEEE802.3at compatible)		
Audio	2ch		
IP Streaming	Yes		
External Sync In	Yes		No
AC adapter	DC12 V		
Ceiling Mount	Yes		
Tally Lamp	Yes (front)	No	
Option	NDI®* HX	4K upgrade, NDI®* HX	

^{*} NDI® is a registered trademark of NewTek, Inc.

BRC-X400







SRG-X400/SRG-X120







Front Rear Front Rear

©2019 Sony Corporation. All rights reserved.

Reproduction in whole or in part without written permission is prohibited.

Features and specifications are subject to change without notice.

The values for weight and dimensions are approximate.

"SONY", "SXRD" "Z-Phosphor" "Motionflow" and "Remote Commander" are trademarks of Sony Corporation.

All other trademarks are the property of their respective owners.

Please visit Sony's professional website or contact your Sony representative for specific models available in your region.