

Square Caméra 30x30mm VBS

GTC-700UB



- 1/3.2" 1.3Mpx Sony Starvis
- 800 LTV
- VBS output
- Fixed lens 3.6mm
- WDR, 2DNR
- Digital D&N
- Mini Square Camera

Specifications

Image Sensor	1/3.2" Exmor RS Progressive Scan SONY STARVIS CMOS	Privacy Mask	-
Effective Pixels	1.27MP 1297(H) x 977(V)	Image Rotation	OFF, H-FLIP, V-FLIP, HV-FLIP
Max. Video Resolution	Horizontal 800TV Lines	Defog	OFF, AUTO
Type	Board mount lens	Sharpness	0-255
Lens Focal Length	3.6mm, F 2.0	OSD control	JOYSTICK
Angle of View	94.91 (D)x81.9 (H)x66.5 (V)	Language	-
Min.Illumination	0.2 Lux (30IRE, F2.0, AGC MAX)	Video Output mode	CVBS(1.0Vp-p Composite 75Ω) NTSC/PAL
Gamma	γ=0.45	General	
IR LEDs	-	IP Rating	-
IR Range	-	Operating Temperature	-10°C~+50°C(Humidity less than 80%)
White Balance	ATW / PUSH / USER1 / USER2 / MANUAL / PUSH LOCK	Storage Temperature	-20°C~+60°C(Humidity less than 80%)
Dynamic Range	WDR/BLC WDR / ATR / OFF	Dimension(mm)	30X30mm
	D-WDR OFF / HLC / BLC	Weight	Approx.27.7g
	Level 138.1dB	Power Source	12VDC(±10%)
Electronic Shutter Speed	AUTO or 1/60(50)~1/100,000	Power Consumption	12VDC(±10%), 60mA max.
Digital Slow Shutter(DSS)	-	Option	
Auto Gain Control(AGC)	MIN, 6, 12, 18, 24, 30, 36, 42, 48, MAX	Power Source	
Day&Night	Electronic D&N	Power Consumption	
Noise Deduction	2D-DNR (Y/C, Y, C, OFF)	Lens	Pinhole lens
Motion Detection	-		

Applications :

- UAV, ROV
- Nucléaire
- Aéronautique
- Robotique
- Défense
- Police

