



## SOL-IQbox-Tough Article number: 221816

Camera junction box for Video surveillance, stainless steel, 400x300x200mm

Optimised for outdoor use Electrically prewired for flexible, modular expansion. Stainless steel 316L / EN 1.4404 Cable glands stainless steel Protective class IP66 Impact resistance IK 10, vandalism protected Swivelling door (with door contact switch) incl. service outlet, personal protection Fast, easy installation Wall or mast mounted

Junction box for universal expansion with a variety of components from different manufacturers and in different designs. Additional components can be mounted on TS35 mounting rails without requiring tools.

## Specifications

General Section:		
Housing material:	Stainless steel EN 1.4404	
Housing surface:	Body and door Scotch-Brite® brushed	
Door:	Swivelling, opening angle 120°, left stop	
Exterior dimensions:	400 x 300 x 200mm	
Protective class:	IP66, IK10	
Temperature range:	-40°C to +90°C (housing and seal)	
Voltage input:	230V/50Hz	
Equipment		
Cable glands:	2 x M16x1,5 - stainless steel EN 1.4404	
	10 x M20x1,5 - stainless steel EN 1.4404	
	All cable entries ex works incl. sealing plugs	
Service outlet:	1 x Protective contact outlet, mounted	
Mounting rail:	2 x TS35 with terminals, mounted, 20mm elevated for placing cables underneath	
Security:	1 x door alarm contact, mounted and wired to terminals	
	1 x control cabinet lock, 2 point double bit	
Ventilation:	2 x pressure compensation element (stainless steel EN 1.4305) mounted	
Personnel protection:	FI Circuit breaker Siemens 5SU1354-6KK16	
Accessories:	4 x sealing plugs for mounting drilled holes	
	1x Drilling Guide Label	
Certificates	RoHs, Reach	

## **Optional accessories**

No.:	221844	SOL-WB-ED	Pole mounting stainless steel EN 1.4301
Nr.:	221817	SOL-IQbox-SD	Sunroof stainless steel EN 1.4301