

VM-FHD15FLT

SKU: 238858



15" (38cm) LCD Monitor, Full HD 1920x1080, LED, HDMI. DisplayPort Flush Mount, Touch Screen

Main Features

Professional 15" (38cm) LCD touchscreen monitor

Designed for continuous operation 24x7x365 (industry level)

Maximum resolution 1920x1080 pixels

LED backlight

Short response time of 5ms

Optimum display thanks to digital 3D filtering

Viewing angle 178° horizontal and vertical

Contrast ratio typically 1,000:1

Versatile video inputs HDMI, DP

Integrated speakers

Operating voltage: 12VDC, external power supply included in d

Flush mount metal housing with white plastic cover

Specifications

General:	
Dimensions (HxWxD)	270x389x40,5mm
Mount	VESA standard 100x100mm, VESA standard 75x75mm
Series	eneo Monitor
Housing color	white
Housing material	Metal
Loudspeaker	nein
Supply voltage	12VDC
Power consumption	approx. 13W
Operating temperature	-30°C ~ +85°C

VM-FHD15FLT

Continuation of the specifications

Weight	5,0kg
Display:	
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Resolution Pixels	1920x1080
Backlighting	LED
Screen size (inch)	15"
Screen size (cm)	38 cm
Aspect ratio	16:9
Viewing angle vertical	178°
Viewing angle horizontal	178°
Brightness typical	300 cd/m ²
Contrast ratio typical	1000:1
Reponse time typical	5 ms
Refresh rate	60 Hz
Functions:	
Comb filter	3D comb filter with de-interlace
Menu languages	English, German, Italian, Spanish, French, Chinese, Russian
Parts supplied:	
Parts supplied	manual, power cord, Acrylic front cover, Power supply unit 100 ~ 240VAC / 12VDC, 50/60Hz, HDMI cable, Thumbscrews for front cover
Interfaces / Inputs/ Outputs:	
Video inputs (type)	DisplayPort, HDMI, USB2.0
Video outputs	no
Audio inputs	no
Serial interfaces	no
Video:	
Resolution	1920x1080 (16:9)
Other	
Display element	Color TFT-LED
Manufacturer order number	238858

VM-FHD15FLT

Technical Drawing

Maße / Dimensions: mm

