



## VM-HD19P

Article number: 224195

19" (48cm) LCD Monitor HD 1280x1024, LED, HDMI, VGA, Composite

Professional 19" (48 cm) LCD monitor

Industrial design built to run 24x7x365 continuously

Maximum resolution 1280x1024 pixels

LED Back Light

Fast response time 5ms

Perfect presentation through digital 3D filtering and noise reduction

Different video inputs HDMI, VGA, Composite

Built-in speakers

Supply Voltage: 12VDC

Plastic cabinet including stand

## Specifications

Display:	
Resolution	1280x1024 (5:4)
Synchronization	internal
Aspect ratio	5:4
Resolution pixels	1280x1024
Display element	Colour TFT/LCD, Anti-Glare-Display, Hard coating (3H), Haze : 3%
Contrast ratio typical	1000:1
Response time typical	5 ms
Brightness typical	300 cd/m²
Backlighting	LED
Viewing angle vertical	178 °
Viewing angle horizontal	178 °
Screen size	19"
Screen Size (cm)	48 cm
Pixel format	0,294mm x 0,294mm
Pixel fault class	ISO 13406-2, Class II
Video standard	PAL/NTSC
Features:	
Comb filter	3D comb filter with de-interlace
Menu languages	English
Interfaces / Inputs / Outputs:	
Video inputs (type)	VGA, HDMI, 2x composite (CVBS)
Audio inputs	1x 3.5mm jack, 1
Audio output	1x 3.5mm jack
Serial interfaces	no
General:	
Dimensions (HxWxD)	350.90x425,1x44,80mm
Total height with stand	408,9mm
Mount	VESA standard 75x75mm
Housing material	plastic
Housing color	black
Weight	3,9kg
Loudspeaker	2
Power consumption	26.5W
Supply voltage	12VDC
Temperature range (operation)	-30°C ~ +85°C, @ Humidity 10%-90% (non-condensing)
Scope of delivery:	
Parts supplied	manual, power cord, PSU 100~240VAC, IR remote controller, VGA cable, feet

## Related Products



VM-TS19A13K0: 228360



eneo is a registered trademark of  
VIDEOR E. Hartig GmbH  
Carl-Zeiss-Straße 8  
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300  
Fax: +49 6074 - 888 - 100  
E-Mail: [info@eneo-security.com](mailto:info@eneo-security.com)  
Web: [www.eneo-security.com](http://www.eneo-security.com)

Stay informed and subscribe  
to the eneo newsletter

